OEM-D4096-960-LC

For customers that prefer to design their own camera solution but do not want to spend time on the sensor integration we offer a range of OEM camera modules

Features

- CMOSIS CMV12000 CMOS image sensor
- 4096 x 3072 pixel resolution
- Suitable for standard and low light applications
- Up to 8.5 / 67fps @ full resolution
- HighSpeed Burst recording mode
- Sensor Binning and X/Y Decimation
- Global shutter
- Available in monochrome, NIR and color
- Extended sensor and camera features
- Up to 10bit greyscale resolution
- Camera level solution available
- Perfect fit for embedded solutions
- Parallel interface



© Photonfocus AG. All rights reserved. This datasheet is subject to change by Photonfocus at any time without any prior notice and Photonfocus cannot be held responsible for any technical or typographical errors.

Quantum Efficiency Image Sensor



Image Sensor Specifications

Manufacturer / Type	CMOSIS, CMV12000
Technology	CMOS
Optical format	APS-like
Optical diagonal	28.14mm
Resolution	4096 x 3072
Pixel size	5.5µm x 5.5µm
Active optical area	22.5mm x 16.9mm
Dark current	125e-/s
Read out noise	13e-
Full well capacity / SNR	11ke- / 105:1
Spectral range	Monochrome: 370 to 900nm (to 10% of peak responsivity)
Responsivity	Monochrome: 1100 x 10^3 DN / (J/m²) @ 520nm / 8bit
Quantum Efficiency	Monochrome: < 45%
Optical fill factor	42% without micro lenses
Dynamic range	60dB
Characteristic curve	Linear, Piecewise linear
Shutter mode	Global shutter

© Photonfocus AG. All rights reserved. This datasheet is subject to change by Photonfocus at any time without any prior notice and Photonfocus cannot be held responsible for any technical or typographical errors.

Camera Specifications

Interface	LVCMOS
Frame rate	8.5 / 67fps
Pixel clock	80MHz
Camera taps	2
Greyscale resolution	8Bit / 10Bit
Fixed pattern noise (FPN)	< 1DN RMS @ 8Bit
Exposure time range	51µs - 419ms
Analog gain	yes
Digital gain	0.1 to 15.99 (FineGain)
Trigger Modes	Free running (non triggered), external Trigger, SWTrigger
Features	Configurable region of interest (ROI), Up to 32 regions of interest (MROI), Sensor Binning and X/Y Decimation, HighSpeed Burst recording mode, 2 look-up tables (12-to-8Bit) on user-defined image region (Region-LUT), Constant frame rate independent of exposure time, Crosshairs overlay on the image, Temperature monitoring of camera, Camera informations readable over SDK, Ultra low trigger delay and low trigger jitter, Extended trigger input and strobe output functionality, Status line in picture
Operation temperature / moisture	0°C ... + 50°C / 20% ... 80%
Storage temperature / moisture	-25°C ... 60°C / 20% ... 95%
Power supply	details in the manual
Power consumption	< 8.5W
Lens mount	n/a
I/O Inputs	details in the manual
I/O Outputs	details in the manual
Dimensions	44 x 44 x 19mm³
Mass	40g
Connector I/O (Power)	n/a
Connector Interface	DF17 series (mating plug DF17(4.0)-80DS-0.5V)
Conformity	CE / RoHS / WEEE
IP Code	IP20

© Photonfocus AG. All rights reserved. This datasheet is subject to change by Photonfocus at any time without any prior notice and Photonfocus cannot be held responsible for any technical or typographical errors.

Connectors

Hirose DF17 series, 80 contacts

Header Photonfocus side \ Receptable Customer side		DF17(?.?)-80DS-0.5V	
		3 mm	4 mm
DF17(2.0)-80DP-0.5V	2 mm	mating height 5 mm (not recommended)	mating height 6 mm

Dimensions







© Photonfocus AG. All rights reserved. This datasheet is subject to change by Photonfocus at any time without any prior notice and Photonfocus cannot be held responsible for any technical or typographical errors.

Explanation

DN DigitalNumber (equals to LSB)

e^- Electrons

Order Information

OEM-D4096-960-LC-10	BW model

Compatibility

Photonfocus AG
Bahnhofplatz 10
CH-8853 Lachen SZ
Switzerland

Phone: +41 55 451 00 00
www.photonfocus.com
info@photonfocus.com

© Photonfocus AG. All rights reserved. This datasheet is subject to change by Photonfocus at any time without any prior notice and Photonfocus cannot be held responsible for any technical or typographical errors.